

Paryavaran Bhawan,
CGO Complex, Lodi Road,
New Delhi - 110 003.

Dated: 10th August, 2009.


To
M/s. Shristi Riverine Limited,
69, Haripriya Abash, 2nd Floor,
Lamb Road, Ambari,
Guwahati - 781 001.

Subject: Development of township at Noonmati, Guwahati, Assam
by M/s. Shristi Riverine Pvt. Ltd. - Environmental
Clearance - Reg.

Dear Sirs,

This has reference to your application No: S13/MoEF/137/07-08, dated 27.12.2007 and subsequent letters dated 25.11.2008, 13.01.2009 and 12.06.2009 seeking prior Environmental Clearance for the above project under the EIA Notification, 2006. The proposal has been appraised as per prescribed procedure in the light of provisions under the EIA Notification, 2006 on the basis of the mandatory documents enclosed with the application viz., the Questionnaire, EIA, EMP and the additional clarifications furnished in response to the observations of the Expert Appraisal Committee constituted by the competent authority in its meetings held on 26th - 27th May 2008, 15th April, 2009 and 18th - 19th June, 2009 and awarded "Silver" grading to the project.

2. It is interalia, noted that the project involves the development of township on a plot area of 101.28 ha. It is proposed to develop 229 plots, low rise apartments - 1260, high rise apartments - 2520 and EWS houses - 1082. The proposal will also have a 120 Bedded hospital, 550 rooms hotel, 215 seats restaurants, High school, Intermediate residential school and a Primary school. The township will have a riverfront laser sports facility with a golf course, retails and commercial facilities. The total water requirement is 4454 KLD. The capacity of 3 STPs proposed is 1860 KLD (2 x 900 KLD + 1 x 60 KLD). Treated waste water to be used for golf course, recreational areas and AC cooling. Total solid waste generation will be 11.89 ton/day (organic - 8.37 ton/day and inorganic - 2.58 ton/day and recyclable waste - 0.94 ton/day). Incinerator will be provided for the treatment and disposal of bio-medical waste (270 Kg/day). The power requirement is 43 MW. The total parking spaces proposed are for plotted development - 688 ECS (surface), low rise apartments - 2268 ECS (surface + still) and high rise apartments - 3276 ECS (surface - 328; still - 490,



- (vi) Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- (v) Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- (iv) All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
- (iii) A First Aid Room will be provided in the project both during construction and operation of the project.
- (ii) Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
- (i) "Consent for Establishment" shall be obtained from Assam Pollution Control Board under Air and Water Act and a copy shall be submitted to the Ministry before start of any construction work at the site.


I. Construction Phase

PART A - SPECIFIC CONDITIONS

3. The Expert Appraisal Committee, after due consideration of the relevant documents submitted by the project proponent and additional clarifications furnished in response to its observations, have recommended for the grant of Environmental Clearance for the project mentioned above. Accordingly, the Ministry hereby accord necessary Environmental Clearance for the above project as per the provisions of Environmental Impact Assessment Notification - 2006 and its subsequent amendments, subject to strict compliance of the terms and conditions as follows:

basement 1 - 1229; basement 2 - 1229) and EWS - 649 ECS, Institutions - 480 cars and 36 buses; for commercial - 2609 ECS; hospitality - 1245 ECS; golf courts - 102 ECS and riverfront laser sports - 269 ECS. Total cost of the project is Rs. 103.00 Crores.

- (vii) Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate watercourses and the dump sites for such material must be secured so that they should not leach into the ground water.
- (viii) Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the Assam Pollution Control Board.
- (ix) The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- (x) The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- (xi) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- (xii) Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/APCB.
- (xiii) Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003. As the site is located within the 100 Km of Thermal Power Stations.
- (xiv) Ready mixed concrete must be used in building construction.
- (xv) Storm water control and its re-use as per CGWB and BIS standards for various applications.
- (xvi) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- (xvii) Permission to draw ground water shall be obtained from the competent Authority prior to construction/operation of the project.



from STP.

The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Treated effluent emanating from STP shall be recycled/reused to the maximum extent possible. Treatment of 100% grey water by decentralised treatment should be done. Discharge of unused treated effluent shall conform to the norms and standards of the Assam Pollution Control Board. Necessary measures should be made to mitigate the odour problem

i)

Operation Phase

II.

(xxv) Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.

(xxiv) Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.

(xxiii) The approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightning etc.


(xxii) Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all airconditioned spaces while it is aspirational for non-airconditioned spaces by use of appropriate thermal insulation material to fulfill requirement.

(xxi) Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.


(xx) Use of glass may be reduced by upto 40% to reduce the electricity consumption and load on airconditioning. If necessary, use high quality double glass with special reflective coating in windows.

(xix) Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

(xviii) Separation of grey and black water should be done by the use of dual plumbing line for separation of grey and black water.



- ii) The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry / inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
- iii) Diesel power generating sets proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use of low sulphur diesel. The location of the DG sets may be decided with in consultation with Assam Pollution Control Board.
- iv) Noise should be controlled to ensure that it does not exceed the prescribed standards. During night time the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.
- v) The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
- vi) Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
- vii) Rain water harvesting for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The borewell for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- viii) The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- ix) Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- x) A Report on the energy conservation measures conforming to energy conservation norms finalise by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Ministry in three months time.



6. The Ministry reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.

5. In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Ministry.


4. Officials from the Regional Office of MOEF, Shillong, who would be monitoring the implementation of environmental safeguards should be given full cooperation, facilities and documents / data by the project proponents during their inspection. A complete set of all the documents submitted to MOEF should be forwarded to the CCF, Regional office of MOEF, Shillong.

ii) The project proponent shall also submit six monthly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB.

i) The environmental safeguards contained in the EIA Report should be implemented in letter and spirit.

PART - B. GENERAL CONDITIONS

- xv) The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
- xiv) Adequate measures should be taken to prevent odour problem from solid waste processing plant and STP.
- xiii) Efforts may be made to use solar energy to the maximum extent possible.
- xii) Central air-conditioning energy efficient system having at least 3 star rating of BEE may be providing for the proposed township.
- xi) Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.



7. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained, as applicable by project proponents from the respective competent authorities.

8. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.

9. The project proponent should advertise in at least two local Newspapers widely circulated in the region, one of which shall be in the vernacular language informing that the project has been accorded Environmental Clearance and copies of clearance letters are available with the Assam Pollution Control Board and may also be seen on the website of the Ministry of Environment and Forests at <http://www.envfor.nic.in>. The advertisement should be made within 10 days from the date of receipt of the Clearance letter and a copy of the same should be forwarded to the Regional office of this Ministry at Shillong.

10. Environmental clearance is subject to final order of the Honble Supreme Court of India in the matter of Goa Foundation Vs. Union of India in Writ Petition (Civil) No.460 of 2004 as may be applicable to this project.

11. Any appeal against this Environmental Clearance shall lie with the National Environment Appellate Authority, if preferred, within a period of 30 days as prescribed under Section 11 of the National Environment Appellate Act, 1997.

12. A copy of the clearance letter shall be sent by the proponent to concerned Panchayat, Zilla Parishad/Municipal Corporation, Urban Local Body and the Local NGO, if any, from whom suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the company by the proponent.

13. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.

14. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF by e-mail.

Copy to:

1. The Secretary, Department of Environment, Government of Assam, Guwahati.
2. The Chairman, Central Pollution Control Board, Parivesh Bhawan, CBD-cum-Office Complex, East Arjun Nagar, Delhi - 110 032.
3. Member Secretary, Assam Pollution Control Board, Guwahati.
4. The CCF, Regional Office, Ministry of Environment & Forests (NEZ), Upianda Road, Laitumkhrah, Shillong - 793003.
5. IA - Division, Monitoring Cell, MOEF, New Delhi - 110003.
6. Guard file.

(Bharat Bhushan)

Director (IA)

(Bharat Bhushan)
Director (IA)